

I claim:

1. An attachment holder, for use with mixing appliance attachments, each attachment including an attachment tool, a shaft with a bore attached to said tool, and an L shaped slot in said shaft, the attachment holder comprising:

a base member with a top side and a bottom side, and a left end and a right end, configured for removable mounting adjacent to an underside of a flat surface;

a plurality of guide dowels attached to said top side of said base member, each post configured for a friction fit with an attachment shaft, and a retaining pin for interfitting engagement with said L shaped slot on said attachment;

at least one generally flat insertion tab attached to said base member adjacent to said bottom side, and parallel to said bottom side, for removable engagement with a mounting bracket, and for use as a stabilizer when said base member is removed from said mounting bracket and placed in an inverted position on a counter;

said mounting bracket being configured for mounting to the underside of a cabinet, and for sliding engagement with said generally flat insertion tab, and including at least one slot for engagement of said at least one insertion tab of said base member.

2. The attachment holder of claim 1, in which said guide dowels are configured for a friction fit with said attachment shaft, in addition to the interfitting engagement with the L shaped slot on the attachment.

3. The attachment holder of claim 1, which further includes at least one generally flat base plate attached to said base member adjacent to said bottom side.

4. The attachment holder of claim 3 which said base plate is configured for use as a stabilizer when said base member is removed from said mounting bracket and placed in an upright position on a countertop.

5. An attachment holder, for use with mixing appliance attachments, each attachment including a shaft with a bore, and an L shaped slot, the attachment holder comprising:

a base member with a top side and a bottom side, and a left end and a right end, configured for mounting adjacent

a plurality of guide dowels attached to said top side of said base member, each post configured for a friction fit with an attachment shaft, and a retaining pin for interfitting engagement with said L shaped slot on said attachment;

a generally flat base plate attached to said base member adjacent to said bottom side, and parallel to said bottom side, for removable engagement with a mounting bracket, and for use as a stabilizer when said base member is removed from said mounting bracket and placed in an inverted position on a counter; and

said mounting bracket being configured for mounting to the underside of a cabinet, and for sliding engagement with said generally flat base plate.

6. The attachment holder of claim 5 in which said mounting bracket is generally U shaped, with a bracket spine with a first end and a second end, with a left mounting pad attached to said first end, and a right mounting pad attached to said second end, with said mounting pads defining a space between them for insertion of said base plate of said base member.

7. The attachment holder of claim 6 in which said left and right mounting pads define one of more openings for mounting screws.